



Page 1/9

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/22/2023 Reviewed on 05/05/2023

### 1 Identification

#### - Product identifier

- Trade name: ND Microspheres® Epoxy Series

- Synonyms: 1193S Orange Microspheres

- Part number: 1193S

- Application of the substance / the mixture Thread Locking

#### - Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA

Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department
- Emergency telephone number: United States: 1-800-424-9300

United States: 1-800-424-9300 International: +1-703-527-3887

### 2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.




GHS08 Health hazard

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated

exposure.



Eye Damage 1 H318 Causes serious eye damage.



Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.
Skin Irritation 2 H315 Causes skin irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

### - Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
  - Hazard pictograms









GHS02 GHS05 GHS07 GHS08

- Signal word Danger
- Hazard-determining components of labeling:

toluene Curing Agent Epoxy resin

Printing date 08/22/2023 Reviewed on 05/05/2023

Trade name: ND Microspheres® Epoxy Series

(Contd. of page 1)

#### Reactive Stabilizer

_	Ha	72	rd	6	fot	·~	m	٦n	te

H225	Highly flammable liquid and vapor.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

#### - Precautionary statements

	otatomonto
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P312 Call a poison center/doctor if you feel unwell.

P362+P364
P333+P313
P403+P233
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### - Other hazards

#### - Results of PBT and vPvB assessment

- PBT: Not applicable.- vPvB: Not applicable.

### 3 Composition/information on ingredients

#### - Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous	components:	
CAS: 108-88-3	toluene	
	Flammable Liquids 2, H225; Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	
CAS: 25036-13-9	Polyoxymethylene melamine urea	20 – 29%
	Skin Irritation 2, H315	
CAS: 28064-14-4	Epoxy resin	20 – 29%
	Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	
CAS: 1761-71-3	Curing Agent	10 – 19%
	Specific Target Organ Toxicity - Repeated Exposure 2, H373; Skin Corrosion 1B, H314; Acute Toxicity - Oral 4, H302; Sensitization - Skin 1, H317	
CAS: 63148-65-2	Binding agent	1 – 4%
	Combustible Dust	
	Reactive Stabilizer	
	Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 2, H330; Skin Corrosion 1B, H314; Eye Damage 1, H318; Acute Toxicity - Oral 4, H302	

#### 4 First-aid measures

#### - Description of first aid measures

- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

## Safety Data Sheet

Printing date 08/22/2023 Reviewed on 05/05/2023

Trade name: ND Microspheres® Epoxy Series

(Contd. of page 2)

#### - After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
  - Most important symptoms and effects, both acute and delayed No further relevant information available.
  - Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

#### - Extinguishing media

- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
  - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### 6 Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

#### Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

## - Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

#### - Handling:

### - Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

No special precautions are necessary if used correctly.

#### - Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

#### - Conditions for safe storage, including any incompatibilities

- Storage:
  - Requirements to be met by storerooms and receptacles: No special requirements.
  - Information about storage in one common storage facility: Not required.
  - Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.

## Safety Data Sheet

Printing date 08/22/2023 Reviewed on 05/05/2023

Trade name: ND Microspheres® Epoxy Series

(Contd. of page 3)

#### - Control parameters

#### - Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### CAS: 108-88-3 toluene

PEL Long-term value: 200 ppm Ceiling limit value: 300; 500\* ppm \*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm

BEI, OTO, A4

#### - Ingredients with biological limit values:

#### CAS: 108-88-3 toluene

BEI 0.02 mg/L Medium: blood

Time: prior to last shift of workweek

0.03 mg/L Medium: urine

Parameter: Toluene

Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

- Additional information: The lists that were valid during the creation were used as basis.

#### - Exposure controls

## - Personal protective equipment:

#### - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### - Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

## - Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### - Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

#### - Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### - Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

(Contd. on page 5)

Printing date 08/22/2023 Reviewed on 05/05/2023

Trade name: ND Microspheres® Epoxy Series

(Contd. of page 4)

## 9 Physical and chemical properties

or nyolour und ollowide proportion				
- Information on basic physical and chemical properties				
- General Information				
- Appearance:				
- Form:	Fluid			
- Color:	Orange			
- Odor:	Solvent-like			
- Odor threshold:	Not determined.			
- pH-value:	Not determined.			
	Not determined.			
- Change in condition				
- Melting point/Melting range:	Undetermined.			
- Boiling point/Boiling range:	≥ 110 – ≤ 111 °C (≥ 230 – ≤ 231.8 °F)			
- Flash point:	4 °C (39.2 °F)			
- Flammability (solid, gaseous):	Highly flammable.			
- Ignition temperature:	535 °C (995 °F)			
- Decomposition temperature:	Not determined.			
- Auto igniting:	Product is not selfigniting.			
- Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.			
- Explosion limits:	F			
- Lower:	1.2 Vol %			
- Lower. - Upper:	7 Vol %			
- Vapor pressure at 20 °C (68 °F):	n.a. hPa			
	II.a. IIra			
- Density at 20 °C (68 °F):	~ 1.05 g/cm³ (~ 8.76225 lbs/gal)			
- Relative density	Not determined.			
- Vapor density	Not determined.			
- Evaporation rate	Not determined.			
- Solubility in / Miscibility with				
- Water:	Not miscible or difficult to mix.			
- Partition coefficient (n-octanol/wa	ater): Not determined.			
- Viscosity:	·			
- Dynamic:	Not determined.			
- Kinematic at 40 °C (104 °F):	1,100 mm²/s			
. ,	1,100 11111 /3			
- Solvent content:	40.00%			
- Organic solvents:	40.2 %			
- Water:	0.1 %			
- VOC content:	40.22 %			
	~ 422.3 g/l / ~ 3.52 lb/gal			
- Solids content:	49.1 %			
- Other information	No further relevant information available.			

## 10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
  - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

Aldehyde

Hydrocarbons

Printing date 08/22/2023 Reviewed on 05/05/2023

Trade name: ND Microspheres® Epoxy Series

(Contd. of page 5)

## 11 Toxicological information

#### - Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:						
ATE (Acut	ATE (Acute Toxicity Estimate)					
Oral	LD50	4,955 mg/kg				
Dermal	LD50	102,041 mg/kg (rabbit)				
Inhalative	LC50/4 h	10.2 mg/l				
CAS: 108-	-88-3 tolue	ene				
Oral	LD50	5,000 mg/kg (rat)				
Dermal	LD50	12,124 mg/kg (rabbit)				
Inhalative	LC50/4 h	5,320 mg/l (mouse)				
CAS: 176	CAS: 1761-71-3 Curing Agent					
Oral	LD50	500 mg/kg (ATE)				
Reactive Stabilizer						
Oral	LD50	790 mg/kg (rat)				
Dermal	LD50	500 mg/kg (rabbit)				
Inhalative	LC50/4 h	0.05 mg/l (ATE)				

#### - Primary irritant effect:

- on the skin: Caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization: Sensitization possible through skin contact.

#### - Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

#### - Carcinogenic categories

- IAR	C (International Agency for Research on Cancer)			
CAS: 108-88-3	toluene	3		
CAS: 7631-86-9	Silicon dioxide, Untreated fumed	3		
CAS: 1309-37-1	Pigment Red	3		
- NTP (National Toxicology Program)				
None of the ingredients is listed.				
- OSHA-Ca (Occupational Safety & Health Administration)				
None of the ingredients is listed.				

#### 12 Ecological information

- Toxicity
  - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
  - Bioaccumulative potential No further relevant information available.
  - Mobility in soil No further relevant information available.
- Ecotoxical effects:
  - Remark: Harmful to fish
- Additional ecological information:
  - General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

## - Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

Printing date 08/22/2023 Reviewed on 05/05/2023

Trade name: ND Microspheres® Epoxy Series

(Contd. of page 6)

## 13 Disposal considerations

- Waste treatment methods
  - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
  - Recommendation: Disposal must be made according to official regulations

- <b>Recommendation:</b> Disposal must be made according to official regulations.				
14 Transport information				
- UN-Number - DOT, IMDG, IATA	UN1133			
- UN proper shipping name - DOT - IMDG, IATA	Adhesives ADHESIVES			
- Transport hazard class(es) - DOT				
- Class - Label	3 Flammable liquids 3			
- IMDG, IATA				
- Class - Label	3 Flammable liquids 3			
- Packing group - DOT, IMDG, IATA	II			
- Environmental hazards: - Marine pollutant:	No			
- Special precautions for user - EMS Number:	Warning: Flammable liquids F-E,S-D			
- Transport in bulk according to Annex II and the IBC Code	of MARPOL73/78 Not applicable.			

# - UN "Model Regulation": 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
  - Sara

Cara
- Section 355 (extremely hazardous substances):
None of the ingredients is listed.
- Section 313 (Specific toxic chemical listings):
CAS: 108-88-3 toluene
- TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.
- Hazardous Air Pollutants
CAS: 108-88-3 toluene

UN 1133 ADHESIVES, 3, II

- Proposition 65

- Chemicals known to cause cancer:
- None of the ingredients is listed.
  - Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Printing date 08/22/2023 Reviewed on 05/05/2023

Trade name: ND Microspheres® Epoxy Series

(Contd. of page 7) - Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. Chemicals known to cause developmental toxicity: CAS: 108-88-3 toluene

- Carcinogenic categories

- EPA	(Environmental Protection Agency)	
CAS: 108-88-3	oluene	II
- TLV	(Threshold Limit Value)	
CAS: 108-88-3	toluene	A4
CAS: 1309-37-1	Pigment Red	A4
- NIO	SH-Ca (National Institute for Occupational Safety and Health)	
None of the ingre	edients is listed.	

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
- Classification System:
  - HMIS-ratings (scale 0 4)



- NFPA ratings (scale 0 - 4)



Health = 3 Fire = 3 Reactivity = 0

- Date of preparation / last revision 08/22/2023
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Oral 4: Acute toxicity - Category 4
Acute Toxicity - Dermal 3: Acute toxicity - Category 3
Acute Toxicity - Inhalation 2: Acute toxicity - Category 2

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Damage 1: Serious eye damage/eye irritation – Category

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Sensitization - Skin 1: Skin sensitisation – Category 1

Toxic to Reproduction 2: Reproductive toxicity - Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2
Aspiration Hazard 1: Aspiration hazard - Category 1

#### - \* Data compared to the previous version altered.

#### Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

Printing date 08/22/2023 Reviewed on 05/05/2023

Trade name: ND Microspheres® Epoxy Series

(Contd. of page 8)